

Time and light control

Digital astro-timers, DIN rail, Yearly program



talento smart C15



talento smart C25

Description

- Digital DIN-rail timer with 500 memory spaces for creating 50 date-specific programmes (ON, OFF Cycle, Impulse, Random ON, Random OFF) and 50 date-independent programmes (ON, OFF Cycle, Impulse, Random ON, Random OFF) with a minimum switching time of 1 minute (ON/OFF) or 1 second (cycle, impulse). Free weekday block formation. Summer/winter time adjustment can be automatic, date-specific or deactivated. 12/24 h setting. Switching state display. Integrated hours counter with maintenance

mode. Manual switch: Automatic, Fix ON/OFF, Override. White display lighting makes it easy to read. Non-volatile memory (EEPROM) for storing programmes in the event of a power outage. Power reserve via battery of up to eight years. The clock can be sealed and can be protected with a PIN to prevent unauthorised access. Programming is performed either directly on the clock or conveniently by means of mobile devices and the corresponding apps (Android and iOS) and PC software

talento smart C15

- 1 channel

talento smart C25

- 2 channels

Product selection

Program	Functions	Channels	Operating voltage	Type	Article number
Astronomical program, yearly program	ON-OFF, Pulse, Cycle	1	110-230 V AC	talento smart C15	43.03.0001.1
		2	110-230 V AC	talento smart C25	43.03.0002.1
			12-24 V AC/DC	talento smart C25 24V	43.03.0003.1


Time and light control

Digital astro-timers, DIN rail, Yearly program


Technical data

	talento smart C15/C25	talento smart C25 24V
Operating voltage	110–230 V AC	12–24 V AC/DC
Frequency	50–60 Hz	
Width	2 modules	
Installation type	DIN rail	
Type of contact	Changeover contact	Changeover contact/NO contact
Power reserve	8 years	
Switching capacity at 250 V AC, cos phi = 1	16 A	
Switching capacity at 250 V AC, cos phi = 0,6	10 A	
Incandescent/halogen lamp load	2600 W	
Energy saving lamps	1000 W	
LED lamps < 2 W (typ.)	100 W	
LED lamps > 2 W (typ.)	600 W	
Shortest switching times	1 min	
Time accuracy at 25 °C	typically $\pm 0,3$ s/day (Quartz)	
Stand-by consumption	< 1 W	
Type of protection	IP 20	
Protection class	II according to EN 60 730-1	
Ambient temperature	–20 °C ... +55 °C	


Connection examples



talento smart C15



talento smart C25



talento smart C25 24V